

# LS Tractor

## MT573C / MT573CPS COMPARISON



MAKE	LS TRACTOR	CASE IH	JOHN DEERE	KUBOTA	MAHINDRA	MASSEY FERGUSON
MODEL	MT573C / MT573CPS (2017-Present)	Farmall 75C (2015-Present)	5075E FT4 (2015-Present)	M4-071 / M4D-071 (2019-Present)	6075 (2018-Present)	MF 4707 (2017-Present)
<b>ENGINE PERFORMANCE</b>						
Advertised Engine Power, Rated, hp (kW)	73 (54.4)	74 (55)	73 (55)	73.2 (54.6)	71 (53)	70 (52.2)
Fuel Tank capacity, gal (L)	26.4 (100)	23.8 (90)	18 (68) open ROPS; 21.6 (82) Cab	23.8 (90)	23.8 (90)	27.7 (105)
<b>PTO PERFORMANCE</b>						
PTO Horsepower, Basic / Optional Transmission, hp (kW)	62 (46)	64 (48)	57 (43)	60 (45)	61 (45.5)	58 (43.2)
PTO Speeds, rpm	540 / 540E / 1000	540 std; 540/540E opt.	540 std.; 540/540E opt.	540 on std.; 540 / 540E on Deluxe	540 and 540E	540 / 1000 std; 540E opt.
<b>BASIC ENGINE</b>						
Engine Make	LS Mtron	Case IH FPT	John Deere	Kubota	Mahindra	Agco Power
Displacement, cu in (L)	153 (2.505)	207 (3.4)	179 (2.9)	203 (3.331)	161.7 (2.649)	201 (3.3)
<b>BASIC TRANSMISSION CONFIGURATION</b>						
Transmission Type	Fully synchronized	4 synchronized gears, 2 ranges	Partially synchronized	6 speeds with high & low	5 gears in each of 3 ranges	2 ranges, mechanical shuttle
Number of Forward / Reverse Speeds	20F / 20R	8F / 8R	9F / 3R	F12 / R12	15F / 15R	8F / 8R
Creeper Range Available	Standard	See option	Creeper gear kit optional	See Creeper option	No	Optional
<b>OPTIONAL TRANSMISSION 1</b>						
Transmission Type	Fully synchronized	4 gears, 3 ranges	Electrohydraulic Reverser	6 creeper speeds	No option	Electro-hydraulic shuttle
Number of Forward / Reverse Speeds	20F / 20R	12F / 12R	12F / 12R	18F / 18R	No option	12F / 12R
<b>HYDRAULIC SYSTEM</b>						
Implement Pump Flow, gpm (Lpm)	13.2 (50)	12.5 (47.5)	11.4 (43.1)	16.7 (63)	11.1 (42)	17.2 (65)
Number of Standard Remote Valves	3 rear; 3 forward	2	1 std. rear; 2 max. rear	2 std.; 3rd opt.	2 standard; 3rd optional	1 std; 2nd and 3rd opt.
<b>3-POINT HITCH FEATURES</b>						
3-Point Hitch Category	Category 2	Category 2	Category 2 / Convertible to 1	Category 1 / 2	Category 1 and 2	Category 2
<b>3-POINT HITCH LIFT CAPACITY</b>						
Standard Lift Capacity 24 Inches behind pin, lb (kg)	4,079 (1850)	3,664 (1662)	3,192 (1448)	3,307 (1500)	np	4,850 (2200)
Standard Lift Capacity at lift pin, lb (kg)	6,614 (3000)	4,832 (2192)	3,968 (1800)	4,189 (1900)	4,850 (2200)	np
<b>WHEELBASE / TRACKBASE</b>						
Wheelbase/Trackbase, MFD/4WD or Track, in (mm)	84.6 (2150)	83.9 (2132)	80.7 (2050)	84.1 (2135)	87.4 (2220)	88.6 (2250)
<b>WEIGHT (w/TIRES OR TRACKS)</b>						
Weight, MFD/4WD w/ROPS, lb (kg)	No open ROPS	5,952 (2700)	5,732 (2600)	No open ROPS	6,746 (3060)	7,125 (3232)
Weight, MFD/4WD or Tracks w/Cab, without ballast, lb (kg)	6,620 (3003)	6,239 (2830) w/fuel	7,275 (3300)	M4-071 5,952 (2700); M4D-071 6,008 (2725)	7,495 (3400)	np
<b>TIRE / TRACK SIZE</b>						
Front Tire Size or Track Width, MFD/4WD or Track	11.2-24 Ag	11.2-24, 6PR R1	9.5-24, 6PR R1	320/70 R24, R1W	320/85 R24 Ag or 12.5/80-18 Industrial	320/85 R24 (12.4 R24), R1W
Rear Tire Size or Track Width	16.9-30 Ag	16.9-30, 6PR R1	16.9 - 28 6PR R1	420/75 R34, R1W	460/85 R30 Ag or 16.9-24 Industrial	420/85 R30 (16.9 R30), R1W