

LS Tractor

XJ2025 / XJ2025H COMPARISON



| MAKE MODEL | LSTRACTOR XJ2025 / XJ2025H (2014-Present) | KUBOTA B2601HSD (2019-Present) | MAHINDRA MAX 25XL HST (2019-Present) | MASSEY FERGUSON MF 1526 (2011-Present) |
|---|--|-----------------------------------|---|---|
| ENGINE PERFORMANCE | | | | |
| Advertised Engine Power, Rated, hp (kW) | 24.4 (18.2) | 24.3 (18.1) | 24 (17.9) | 24.8 (18.5) |
| Fuel Tank capacity, gal (L) | 6.6 (25) | 6.1 (23) | 6.1 (23) | 7.1 (27) |
| PTO PERFORMANCE | | | | |
| PTO Horsepower, Basic / Optional Transmission, hp (kW) | 19.5 (14.5) / 18.5 (13.8) | 19.5 (14.5) | 20 (14.9) | 20.1 (15) |
| PTO Speeds, rpm | 540 | 540 | 540 | 540 |
| BASIC ENGINE | | | | |
| Engine Make | Mitsubishi | Kubota | Mitsubishi | Iseki |
| Displacement, cu in (L) | 80.4 (1.318) | 68.5 (1.123) | 80.4 (1.318) | 91.4 (1.50) |
| BASIC TRANSMISSION CONFIGURATION | | | | |
| Transmission Type | Sliding gear | Hydrostatic | Hydrostatic | Hydrostatic |
| Number of Forward / Reverse Speeds | 6F / 2R | Infinite, 3 ranges | Infinite, 2 ranges | Infinite, 3 range |
| Creeper Range Available | No | No | np | Yes, hydrostatic |
| OPTIONAL TRANSMISSION 1 | | | | |
| Transmission Type | Hydrostatic, 2 range | No option | No option | No option |
| Number of Forward / Reverse Speeds | Infinite, 2 ranges | No option | No option | No option |
| HYDRAULIC SYSTEM | | | | |
| Implement Pump Flow, gpm (Lpm) | 6.9 (26) Gear; 5.9 (22) HST | 4.7 (18) | 4.6 (17.5) | 8.7 (32.9) |
| Number of Standard Remote Valves | Optional | 1 or 2 optional | np | np |
| 3-POINT HITCH FEATURES | | | | |
| 3-Point Hitch Category | Category 1 | Category 1 | Category 1 | Category 1 |
| 3-POINT HITCH LIFT CAPACITY | | | | |
| Standard Lift Capacity 24 Inches behind pin, lb (kg) | np | 1,411 (640) | np | 992 (450) |
| Standard Lift Capacity at lift pin, lb (kg) | 1,433 (650) | 1,808 (820) | 1,354 (614) | 1,322 (600) |
| WHEELBASE / TRACKBASE | | | | |
| Wheelbase/Trackbase, MFD/4WD or Track, in (mm) | 59 (1500) | 61.4 (1560) | 58.2 (1480) | 61.4 (1560) |
| WEIGHT (w/TIRES OR TRACKS) | | | | |
| Weight, MFD/4WD w/ROPS, lb (kg) | 1,785 (810) Gear / 1,609 (730) HST | 1,632 (740) | 1,715 (778) | 1,873 (850) |
| Weight, MFD/4WD or Tracks w/Cab, without ballast, lb (kg) | No cab | No cab | No cab | No cab |
| TIRE / TRACK SIZE | | | | |
| Front Tire Size or Track Width, MFD/4WD or Track | 23x8.5-12 Industrial | 7-12, R1 | 6x12 Ag or 20x8-10 Industrial | 7-12, 4PR |
| Rear Tire Size or Track Width | 33x12-16.5 Industrial | 11.2-16, R1 | 9.5x16 Ag or 27x12.5-15 Industrial | 35x12.00-16.5, 4PR |