

| Model | MT226ED | MT226E | MT226HE | MT232E | MT232HE | MT242E | MT242HE | MT226HEC | MT232HEC | MT242HEC | MT232H | MT242H | MT232HC | MT242HC | | |
|--------------------------------------|--|-------------|-------------|---|-------------|---|-------------|---|---|---|---|---|---|---|--|----|
| Type | ROPS Type | | | | | | Cabin Type | | | ROPS Type | | Cabin Type | | | | |
| ENGINE | | | | | | | | | | | | | | | | |
| Type | 3 Cylinder Liquid-cooled Diesel, NA, IDI | | | 3 Cylinder Liquid-cooled Diesel, NA, CRDI | | 4 Cylinder liquid-cooled Diesel, NA, CRDI | | 3 Cylinder Liquid-cooled Diesel, NA, DI | 3 Cylinder Liquid-cooled Diesel, NA, CRDI | 4 Cylinder liquid-cooled Diesel, NA, CRDI | 3 Cylinder Liquid-cooled Diesel, NA, CRDI | 4 Cylinder liquid-cooled Diesel, NA, CRDI | 3 Cylinder Liquid-cooled Diesel, NA, CRDI | 4 Cylinder liquid-cooled Diesel, NA, CRDI | | |
| Model(Tier4) | MHI S3L2-W463GTAC | | | YANMAR 3TNV88C-MLST | | YANMAR 4TNV88C-MLST | | YANMAR 3TNV88F-EPLST | YANMAR 3TNV88C-MLST | YANMAR 4TNV88C-MLST | YANMAR 3TNV88C-MLST | YANMAR 4TNV88C-MLST | YANMAR 3TNV88C-MLST | YANMAR 4TNV88C-MLST | | |
| Engine HP(GROSS) | 24.6 | 24.6 | 24.6 | 31.7 | 31.7 | 42.5 | 42.5 | 24.4 | 31.7 | 42.5 | 31.7 | 42.5 | 31.7 | 42.5 | | |
| PTO HP | 19.2 | 19.2 | 17.1 | 28.5 | 26.2 | 35.4 | 34.8 | 19 | 26.2 | 34.8 | 26.2 | 34.8 | 26.2 | 34.8 | | |
| Rated speed, RPM | 2,500 | 2,500 | 2,500 | 2,600 | 2,600 | 2,600 | 2,600 | 2,400 | 2,600 | 2,600 | 2,600 | 2,600 | 2,600 | 2,600 | | |
| Displacement-cu, in ³ | 80.4 | | | 100.2 | | 133.6 | 133.6 | 100.2 | 100.2 | 133.6 | 100.2 | 133.6 | 100.2 | 133.6 | | |
| Fuel tank capacity (gal) | 10.6 | | | | | | 11.4 | | | 10.6 | | 11.4 | | | | |
| Alternator(V-A) | 12V - 50 Amps | | | 12V - 55 Amps | | | | | | | | | | | | |
| DRIVETRAIN | | | | | | | | | | | | | | | | |
| Transmission | Synchro Shuttle | | HST | Synchro Shuttle | HST | Synchro Shuttle | HST | | | | | | | | | |
| No. of Speed | F12 X R12 | | 3 Ranges | F12 X R12 | 3 Ranges | F12 X R12 | 3 Ranges | | | | | | | | | |
| Brakes | Wet, Multi - disc | | | | | | | | | | | | | | | |
| Steering | Hydrostatic Power Steering | | | | | | | | | | | | | | | |
| PTO | | | | | | | | | | | | | | | | |
| Type | TM Driven | Independent | Independent | Independent | Independent | Independent | Independent | Independent | Independent | Independent | Independent | Independent | Independent | Independent | | |
| Rear(rpm) | Standard (540 rpm) | | | | | | | | | | | | | | | |
| HYDRAULIC SYSTEM | | | | | | | | | | | | | | | | |
| Control System | Position | | | | | | | | | | | | | | | |
| Implement pump, gpm | 7.9 | | 7.1 | 7.4 | 6.7 | 7.4 | 6.7 | 6.1 | 6.7 | | | | | | | |
| Steering pump, gpm | 4.6 | | 5 | | | | | 4.6 | | | 5 | | | | | |
| Total flow, gpm | 12.5 | | 11.7 | 12.4 | 11.7 | 12.4 | 11.7 | 10.7 | | 11.7 | | | | | | |
| Category, 3pt hitch | CAT I | | | | | | | | | | | | | | | |
| Hitch Lift capacity, lbs (Hitch end) | 1,808 lbs | | | 2,756 lbs | | | | 1,808 lbs | | 2,756 lbs | | | | | | |
| Remote valves | Option | | | | | | | | | | 1pair | | | | | |
| DIMENSION | | | | | | | | | | | | | | | | |
| Overall length, Frame to link in. | 119 | | | 125 | | | | | | | | | | | | |
| Overall width tires, in. (Incl Rear) | 66 | | | | | | | | | | | | | | | |
| Wheelbase, in. | 66 | | 69 | | 74 | | | 69 | | 74 | 69 | | 74 | 69 | | 74 |
| Ht to top of rops, in. (Incl tire) | 95 | | | | 90 | | | | | 95 | | 90 | | | | |
| TIRE SIZE | | | | | | | | | | | | | | | | |
| Ag Front / Rear | 7 - 14 / 11.2 - 24 | | | | | | | | | | | | | | | |
| IND Front / Rear | 27X8.50-15 / 43X16.00-20 | | | | | | | | | | | | | | | |
| VT Front / Rear | 27X8.50-15 / 43X16.00-20 | | | | | | | | | | | | | | | |
| Turf Front / Rear | 25X8.50-14 / 41X14.00-20 | | | | | | | | | | | | | | | |
| WEIGHT | | | | | | | | | | | | | | | | |
| Total weight without ballast, lbs. | 2963 | 2985 | 3007 | 3166 | 3210 | 3250 | 3294 | 3609 | 3677 | 3761 | 3254 | 3338 | 3721 | 3805 | | |

Note: Specifications and design are subject to change without prior notice.

IMPLEMENT

| Front end Loader | LL3001, LL3002 |
|---|---------------------------|
| MATCHING TRACTOR | MT226E (ROPS, CAB) |
| Bucket, in. | 66 |
| Maximum Lift height, in. | 94.3 |
| Clearance with Attachment Dump, in. | 67 |
| Reach at Maximum Height, in. | 14.4 |
| Maximum Dump Angle, deg. | 48 |
| Maximum Rollback Angle, deg. | 42.5 |
| Digging Depth, in. | 4.8 |
| Overall Height in Carry Position, in. | 51.2 |
| Lift Capacity (Bucket Pivot Pin, MAX, Height) lbs | 1,599 |
| Lift Capacity (Pivot pin @ 1.5m) lbs | 1,965 |
| Breakout Force(@ Pivot pin), lbs. | 2,962 |
| Approx. Weight (Loader w/o Bucket), lbs. | 741 |

| Front end Loader | LL3003 |
|---|-------------------------------------|
| Matching Tractor | MT232E, MT242E, MT232, MT242 |
| Bucket, in. | 66 |
| Maximum Lift height, in. | 94.3 |
| Clearance with Attachment Dump, in. | 67 |
| Reach at Maximum Height, in. | 14.4 |
| Maximum Dump Angle, deg. | 48 |
| Maximum Rollback Angle, deg. | 42.5 |
| Digging Depth, in. | 4.8 |
| Overall Height in Carry Position, in. | 51.2 |
| Lift Capacity (Bucket Pivot Pin, MAX, Height) lbs | 2,063 |
| Lift Capacity (Pivot pin @ 1.5m) lbs | 2,506 |
| Breakout Force(@ Pivot pin), lbs. | 3,723 |
| Approx. Weight (Loader w/o Bucket), lbs. | 741 |

| Backhoe | LB3001 |
|---|---------------------|
| Matching Tractor | MT226E(ROPS) |
| Digging Depth, in. | 97.2 |
| Reach from centerline of swing Pivot, in. | 127.2 |
| Loading Height, in. | 76.2 |
| Swing Arc, deg. | 160 |
| Transport Height, in. | 81.8 |
| Bucket Rotating, deg. | 180 |
| Stabilizer Spread(Down position), in. | 67.5 |
| Stabilizer Spread(Up position), in. | 50 |
| Bucket Digging force, lbs. | 3,663 |

| Backhoe | LB3002 |
|---|--|
| Matching Tractor | MT226E(CAB), MT232E, MT242E, MT232, MT242 |
| Digging Depth, in. | 97.2 |
| Reach from centerline of swing Pivot, in. | 127.2 |
| Loading Height, in. | 76.2 |
| Swing Arc, deg. | 160 |
| Transport Height, in. | 81.8 |
| Bucket Rotating, deg. | 180 |
| Stabilizer Spread(Down position), in. | 67.5 |
| Stabilizer Spread(Up position), in. | 50 |
| Bucket Digging force, lbs. | 3,663 |

