

COMPACT TRACTORS | 24.7 HP

MT2S SERIES

START BLUE. STAY BLUE.

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

LS Tractor

6-year limited warranty.
See dealer for details.



LS Tractor
Start Blue. Stay Blue.

MT2S SERIES

HIGHER STANDARDS. LOWER ISSUES.


Maintaining your land to your standards takes a tractor and attachments made to ours. And with a six-year limited powertrain warranty on most models,you'll be well taken care of as well.



Premium Reversible Seat
Adjustable foldable armrest, tilt high back seat.
*Reversible seat only on backhoe models



3 Range Hydrostatic Transmission
2 Pedal comfortable and efficient operator control



Bolted Edge Bucket
Built for the harshest conditions



Standard Factory Grille Guard W/ Loader
Full length grille guard protects body panels and radiator



Durability And Capacity
Provides added functionality to the heavy-duty backhoe



Optional Drive-Over Mid-Mount Mower Deck
Providing convenience and ease of adapting to any application



Standard Tilt Steering
Provides enhanced operator comfort



Standard Foldable ROPS
Enables easy adjustment for clearance




Mid-Mount Height Adjustment Dial
Enables precise height control of the mid-mount mower by a single turn

RECOMMENDED IMPLEMENTS / ATTACHMENTS



LOADER
High capacity with an abundance of standard features



BACKHOE
Excellent capacity, smooth and consistent operation for added control



ROTARY CUTTER
Durable heavy steel design providing quality and strength



BOX BLADE
Features a heavy welded steel design for use in demanding applications

MT225S SPECIFICATIONS

CATEGORY	
ENGINE	MT225S
Type	3 Cylinder-IDI
Model (Tier 4)	3TNV80F-ZXKLST (Yanmar)
Engine HP (gross)	24.7
PTO (HP)	19.3
Rated Speed (rpm)	2,800
Displacement-cu (in ³)	77.3
Fuel Tank Capacity (gal.)	6.79
Alternator (V-A)	12 - 40
DRIVE TRAIN	
Transmission	HST
No. Of Speed	3 Ranges
Brakes	Wet, Multi-disc
PTO	
Type	Independent
Rear (rpm)	540
Mid PTO (Option)	2,500
HYDRAULIC SYSTEM	
Lift Control System	Position
Implement Pump (gpm)	5.6
Steering Pump (gpm)	3.7
Steering	Hydrostatic Power Steering
Total Flow (gpm)	9.3
Category (3pt Hitch)	CAT I
Hitch Lift Capacity (lbs.) (Hitch End)	1,896
Remote Valves	1 Pair (Option)
DIMENSION (WITH R1 TIRES)	
Overall Length (Frame To Link in.)	111.9
Overall Width With Tires (in.)	48.7
Wheelbase (in.)	63.4
Height To Top Of ROPS (in.)	86.4
TIRE SIZE	
Front / Rear Ag (R1)	7 - 12 / 11.2 - 16
Front / Rear Industrial (R4)	23 x 8.5 - 12 / 12 - 16.5
Front / Rear Turf (R3)	22 x 8.5 - 12 / 31 x 15.5 - 15
WEIGHT	
Total Weight w/o Ballast (lbs.)	1,764

**All specs and features are subject to change, and pictures could include optional equipment etc.*

- Additional Equipment**
- Standard Factory Toolbox
 - Standard 12 Volt Power Outlet
 - Flat Operator With Rubber Mat
 - Standard Factory Platform Step

FRONT END LOADER	LL2300	LL2001
TRACTOR APPLICATION	MT225S	MT225S
Bucket Size (in.)	54.3	54
Maximum Lift Height (in.)	84.4	84.4
Clearance With Attachment Dump (in.)	59.1	59.1
Reach At Maximum Height (in.)	17.9	17.8
Maximum Dump Angle (deg.)	55	55
Maximum Rollback Angle (deg.)	40	27
Digging Depth (in.)	4.5	4.5
Overall Heights In Carry Position (in.)	46	49.5
Lift Capacity (At Pivot Pin) (lbs.)	1,067	1,127
Breakout Force (At Pivot Pin) (lbs.)	2,290	1,744
Approx. Weight (Loader w/o Bucket) (lbs.)	708	742

BACKHOE	LB1300	LB2100
TRACTOR APPLICATION	MT225S	MT225S
Digging Depth (in.)	84.9	82.6
Reach From Centerline Of Swing Pivot (in.)	113.7	113.5
Loading Height (in.)	64.7	65.8
Swing Arc (deg.)	180	170
Transport Height (in.)	73.4	68.5
Bucket Rotating (deg.)	177	164
Stabilizer Spread (Down Position) (in.)	82.2	57.3
Stabilizer Spread (Up Position) (in.)	65.4	63.9
Bucket Digging Force (lbs.)	3,013	2,897

MID MOWER	LM2360
TRACTOR APPLICATION	MT225S
Cutting Width (in.)	60
Cutting Height Range (in.)	1 - 4
Transport Height (in.)	6
Gear Type	Spiral Bevel
Number Of Blades	3
Adjustment Of Cutting Height	Dial
Deck Thickness (in.)	0.15
Total Width (in.)	75.7
Total Length (w/o Linkage)	44.1
Total Height (w/o Linkage)	11.9
Lifting Type	3-Point Upper Link
Total Weight (lbs.)	368