

COMPACT TRACTORS | 25 HP - 42 HP

# MT2E | MT2 SERIES

# START BLUE. STAY BLUE.

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | [LSTractorUSA.com](http://LSTractorUSA.com)  
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

## LS Tractor

6-year limited warranty.  
See dealer for details.



**LS Tractor**  
Start Blue. Stay Blue.

MT2E | MT2 SERIES

# HIGHER STANDARDS. LOWER ISSUES.

Maintaining your land to your standards takes a tractor and attachments made to ours. And with a six-year limited powertrain warranty on most models, you'll be well taken care of as well.



**NEW LS FAMILY LOOK**  
Upgraded, modern look also provides better functionality



**LED LIGHTS**  
Increased visibility while increasing efficiency



**LARGER TIRE SIZE AND OPTIONS**  
Enhanced traction and stability with more options



**BETTER VISIBILITY**  
Cab redesign allows for better operator visibility



**LOADER LIFT CAPACITY INCREASE**  
Do more work easily



**TF-LCD PANEL**  
Shows regen time, oil change intervals and more



**IMPROVED SEAT COMFORT**  
So you can stay more comfortable for longer



**UPGRADED ERGONOMIC CONTROLS**  
Refined controls make for easier operation




**NEW DEEP SKY BLUE PAINT**  
Elevated look with silver rims

## RECOMMENDED IMPLEMENTS / ATTACHMENTS



**LOADER**  
High capacity with an abundance of standard features



**BACKHOE**  
Excellent capacity, smooth and consistent operation for added control



**ROTARY CUTTER**  
Durable heavy steel design providing quality and strength



**BOX BLADE**  
Features a heavy welded steel design for use in demanding applications

# MT2E / MT2 SPECIFICATIONS

| MODEL                                | MT226ED                    | MT226E                     | MT226HE                    | MT232E                     | MT232HE                    | MT242E                     | MT242HE                    | MT226HEC                   | MT232HEC                   | MT242HEC                   | MT232H                     | MT242H                     | MT232HC                    | MT242HC                    |
|--------------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| Type                                 | ROPS Type                  | ROPS Type                  | ROPS Type                  | ROPS Type                  | ROPS Type                  | ROPS Type                  | ROPS Type                  | Cabin Type                 | Cabin Type                 | Cabin Type                 | ROPS Type                  | ROPS Type                  | Cabin Type                 | Cabin Type                 |
| ENGINE                               |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |
| Type (Liquid-cooled Diesel)          | 3 Cylinder, NA, IDI        | 3 Cylinder, NA, IDI        | 3 Cylinder, NA, IDI        | 3 Cylinder, NA, CRDI       | 3 Cylinder, NA, CRDI       | 4 Cylinder, NA, CRDI       | 4 Cylinder, NA, CRDI       | 3 Cylinder, NA, CRDI       | 3 Cylinder, NA, CRDI       | 4 Cylinder, NA, CRDI       | 3 Cylinder, NA, CRDI       | 4 Cylinder, NA, CRDI       | 3 Cylinder, NA, CRDI       | 4 Cylinder, NA, CRDI       |
| Model (Tier 4)                       | MHI S3L2-W463G-TAC         | MHI S3L2-W463G-TAC         | MHI S3L2-W463G-TAC         | YANMAR 3TN-V88C-MLST       | YANMAR 3TN-V88C-MLST       | YANMAR 4TN-V88C-MLST       | YANMAR 4TN-V88C-MLST       | YANMAR 3TNV88F-EPLST       | YANMAR 3TNV88C-MLST        | YANMAR 4TNV88C-MLST        | YANMAR 3TNV88C-MLST        | YANMAR 4TNV88C-MLST        | YANMAR 3TNV88C-MLST        | YANMAR 4TNV88C-MLST        |
| Engine HP (gross)                    | 24.6                       | 24.6                       | 24.6                       | 31.7                       | 31.7                       | 42.5                       | 42.5                       | 24.4                       | 31.7                       | 42.5                       | 31.7                       | 42.5                       | 31.7                       | 42.5                       |
| PTO (HP)                             | 19.2                       | 19.2                       | 17.1                       | 28.5                       | 26.2                       | 35.4                       | 34.8                       | 19                         | 26.2                       | 34.8                       | 26.2                       | 34.8                       | 26.2                       | 34.8                       |
| Rated Speed (rpm)                    | 2,500                      | 2,500                      | 2,500                      | 2,600                      | 2,600                      | 2,600                      | 2,600                      | 2,400                      | 2,600                      | 2,600                      | 2,600                      | 2,600                      | 2,600                      | 2,600                      |
| Displacement (in <sup>3</sup> )      | 80.4                       | 80.4                       | 80.4                       | 100.2                      | 100.2                      | 133.6                      | 133.6                      | 100.2                      | 100.2                      | 133.6                      | 100.2                      | 133.6                      | 100.2                      | 133.6                      |
| Fuel Tank Capacity (gal.)            | 10.6                       | 10.6                       | 10.6                       | 10.6                       | 10.6                       | 10.6                       | 10.6                       | 11.4                       | 11.4                       | 11.4                       | 10.6                       | 10.6                       | 11.4                       | 11.4                       |
| Alternator V-A                       | 12V - 50 Amps              | 12V - 50 Amps              | 12V - 50 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              | 12V - 55 Amps              |
| DRIVE TRAIN                          |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |
| Transmission                         | Synchro Shuttle            | Synchro Shuttle            | HST                        | Synchro Shuttle            | HST                        | Synchro Shuttle            | HST                        | HST                        | HST                        | HST                        | HST                        | HST                        | HST                        | HST                        |
| No. Of Speed                         | F12 X R12                  | F12 X R12                  | 3 Ranges                   | F12 X R12                  | 3 Ranges                   | F12 X R12                  | 3 Ranges                   | 3 Ranges                   | 3 Ranges                   | 3 Ranges                   | 3 Ranges                   | 3 Ranges                   | 3 Ranges                   | 3 Ranges                   |
| Brakes                               | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            | Wet, Multi-disc            |
| Steering                             | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering |
| PTO                                  |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |
| Type                                 | TM Driven                  | Independent                | Independent                | Independent                | Independent                | Independent                | Independent                | Independent                | Independent                | Independent                | Independent                | Independent                | Independent                | Independent                |
| Rear (rpm)                           | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             | Standard (540)             |
| HYDRAULIC SYSTEM                     |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |
| Control System                       | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   | Position                   |
| Implement Pump (gpm)                 | 7.9                        | 7.9                        | 7.1                        | 7.4                        | 6.7                        | 7.4                        | 6.7                        | 6.1                        | 6.7                        | 6.7                        | 6.7                        | 6.7                        | 6.7                        | 6.7                        |
| Steering Pump (gpm)                  | 4.6                        | 4.6                        | 4.6                        | 5                          | 5                          | 5                          | 4.6                        | 5                          | 5                          | 5                          | 5                          | 5                          | 5                          | 5                          |
| Total Flow (gpm)                     | 12.5                       | 12.5                       | 11.7                       | 12.4                       | 11.7                       | 12.4                       | 11.7                       | 10.7                       | 11.7                       | 11.7                       | 11.7                       | 11.7                       | 11.7                       | 11.7                       |
| Category (3pt Hitch)                 | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      | CAT I                      |
| Hitch Lift Capacity Hitch End (lbs.) | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      | 1,433                      |
| Remote Valves                        | Option                     | Option                     | Option                     | Option                     | Option                     | Option                     | Option                     | 1pair                      | 1pair                      | 1pair                      | 1pair                      | 1pair                      | 1pair                      | 1pair                      |
| DIMENSION                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |
| Overall Length (Frame To Link, in.)  | 119                        | 119                        | 119                        | 125                        | 125                        | 125                        | 125                        | 125                        | 125                        | 125                        | 125                        | 125                        | 125                        | 125                        |
| Overall Width With Tires (in.)       | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         | 66                         |
| Wheelbase (in.)                      | 66                         | 66                         | 66                         | 69                         | 69                         | 74                         | 74                         | 69                         | 69                         | 74                         | 69                         | 74                         | 69                         | 74                         |
| Height To Top ROPS (in.)             | 95                         | 95                         | 95                         | 95                         | 95                         | 95                         | 95                         | 90                         | 90                         | 90                         | 95                         | 95                         | 90                         | 90                         |
| TIRE SIZE                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |
| Front / Rear Ag                      | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         | 7 - 14 / 11.2 - 24         |
| Front / Rear Industrial              | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   |
| Front / Rear VT                      | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   | 27X8.50-15 / 43X16.00-20   |
| Front / Rear Turf                    | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   | 25X8.50-14 / 41X14.00-20   |
| WEIGHT                               |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |                            |
| Total Weight w/o Ballast (lbs.)      | 2963                       | 2985                       | 3007                       | 3166                       | 3210                       | 3250                       | 3294                       | 3609                       | 3677                       | 3761                       | 3254                       | 3338                       | 3721                       | 3805                       |

| FRONT END LOADER                          | LL3001, LL3002     | LL3003                       |
|-------------------------------------------|--------------------|------------------------------|
| MATCHING TRACTOR                          | MT226E (ROPS, CAB) | MT232E, MT242E, MT232, MT242 |
| Bucket Size (in.)                         | 66                 | 66                           |
| Maximum Lift Height (in.)                 | 94.3               | 94.3                         |
| Clearance With Attachment Dump (in.)      | 67                 | 67                           |
| Reach At Maximum Height (in.)             | 14.4               | 14.4                         |
| Maximum Dump Angle (deg.)                 | 48                 | 48                           |
| Maximum Rollback Angle (deg.)             | 42.5               | 42.5                         |
| Digging Depth (in.)                       | 4.8                | 4.8                          |
| Overall Height In Carry Position (in.)    | 51.2               | 51.2                         |
| Lift Capacity (At Pivot Pin, 1.5m) (lbs.) | 1,965              | 2,506                        |
| Breakout Force (At Pivot Pin) (lbs.)      | 2,962              | 3,723                        |
| Approx. Weight (Loader w/o Bucket) (lbs.) | 741                | 741                          |

| BACKHOE                                    | LB3001, LB3002                                            |
|--------------------------------------------|-----------------------------------------------------------|
| TRACTOR APPLICATION                        | MT226E (ROPS), MT226E (CAB), MT232E, MT242E, MT232, MT242 |
| Digging Depth (in.)                        | 922                                                       |
| Reach From Centerline Of Swing Pivot (in.) | 1272                                                      |
| Loading Height (in.)                       | 76.2                                                      |
| Swing Arc (deg.)                           | 160                                                       |
| Transport Height (in.)                     | 81.8                                                      |
| Bucket Rotating (deg.)                     | 180                                                       |
| Stabilizer Spread (Down Position) (in.)    | 675                                                       |
| Stabilizer Spread (Up Position) (in.)      | 50                                                        |
| Bucket Digging Force (lbs.)                | 3,663                                                     |

*\*All specs and features are subject to change, and pictures could include optional equipment etc.*

**Additional Equipment**

- Standard Rear Work-light, ROPS and Cab
- Standard Drawbar