

UTILITY TRACTORS | 63 HP - 73 HP

MT4 SERIES

START BLUE. STAY BLUE.

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

LS Tractor

6-year limited warranty.
See dealer for details.



LS Tractor
Start Blue. Stay Blue.

MT4 SERIES

HIGHER
STANDARDS.
LOWER ISSUES.

Maintaining your land to your standards takes a tractor and attachments made to ours. And with a six-year limited powertrain warranty on most models, you'll be well taken care of as well.




Knob Design Enhancement
Refined controls make for easier operation



Enhanced Steering Grip
Improved ease of operation




Standard TF-LCD Instrument Panel
Shows Regen Time, oil change intervals and more



Loader Lift Capacity Increase
Do more work more easily



New LS Family Look
Upgraded, modern look also provides better functionality



Improved High Back Seat
Wide and improved cushion and comfort



Standard 3rd Function Button on Joystick
Easier and more cost effective when upgrading to 3rd option



Wraparound Style Interior and Exterior
Improved visibility



4 Different Tire Options
Tires to match any application (Including new large Ag style)

RECOMMENDED
IMPLEMENTS /
ATTACHMENTS



LOADER
High capacity with an abundance of standard features



LAND GRADER
Heavy steel construction, high strength designed for use in demanding applications



ROTARY CUTTER
Durable heavy steel design providing quality and strength



BOX BLADE
Features a heavy welded steel design for use in demanding applications

MT4 SERIES SPECIFICATIONS

Model	MT463	MT463PS	MT463C	MT463CPS	MT473	MT473PS	MT473C	MT473CPS
ENGINE								
Type	Vertical Water-Cooled 4Cycle Diesel Engine							
Model (Tier4)	L4C25-T							
Engine HP (gross)	63				73			
PTO (HP)	54.1				62.9			
Rated Speed (rpm)	2,500							
Displacement (in³)	152.85							
Fuel Tank Capacity (gal.) (L)	24.3 (92)							
DRIVE TRAIN								
Transmission	Synchro Shuttle	Electro Power Shuttle	Synchro Shuttle	Electro Power Shuttle	Synchro Shuttle	Electro Power Shuttle	Synchro Shuttle	Power Shuttle
No. Of Speed	F16 x R16							
Brakes	Wet, Multi-disc							
PTO								
Type	Independent							
Rear (rpm)	540, 540E (Std.)							
HYDRAULIC SYSTEM								
Control System	Position / Draft							
Implement Pump (gpm)	14.5							
Steering Pump (gpm)	6.6							
Total Flow (gpm)	21.1							
Category (3pt Hitch)	CAT II							
Hitch Lift Capacity (@610mm, lbs.)	3,483 (@ 24" From The Hitch End)							
Remote Valves	2 Pairs (Front), 2 Pairs (Rear)							
Steering	Hydrostatic Power Steering							
DIMENSION								
Overall length, Bumper To Link (in.)	140							
Overall Width, Tires (in.)	72.6							
Wheelbase (in.)	83.1							
Height To Top Of ROPS/Cab (in.)	113.9	105.4			113.9		105.4	
TIRE SIZE								
Standard Ag Front / Rear	9.5 - 24 / 16.9 - 28							
IND Front / Rear	10.5/80x18 10PR / 19.5Lx24 8PR							
Large Ag Front / Rear	11.2-24 / 16.9-30							
R14 Front / Rear	320/85R20 119D / 420/75R34 142D							
WEIGHT								
Total Weight (W/O Ballast) (lbs.)	5,313	5,776			5,423		5,886	

FRONT END LOADER	LL5001	
TRACTOR APPLICATION	MT4	
	HEIGHT POSITION	POWER POSITION
Bucket Size (in.)	78	78
Maximum Lift Height (in.)	132.9	116.8
Lift Capacity (At Pivot Pin, Max. Height) (lbs.)	3,426	3,488
Maximum Dump Angle (deg.)	44.4	59.7
Bucket Capacity (gal.)	126.8	126.8
Bucket Rollback Force (At Ground Level) (lbs.)	3,524	3,529
Digging Depth (in.)	6	5.1
Loader Weight (W/O Bucket) (lbs.)	1,190	1,190

Note: Specifications and design are subject to change without prior notice.



AVAILABLE IN ROPS & CAB