

UTILITY TRACTORS | 73 HP

MT5 SERIES

START BLUE. STAY BLUE.

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

LS Tractor

6-year limited warranty.
See dealer for details.



LS Tractor
Start Blue. Stay Blue.

MT5 SERIES

HIGHER STANDARDS. LOWER ISSUES.

Maintaining your land to your standards takes a tractor and attachments made to ours. And with a six-year limited powertrain warranty on most models,you'll be well taken care of as well.



Ergonomic Right-Side Console
Provides unobstructed access to control levers



Integrated Loader Joystick
Enables precise control of the front-loader



Position and Draft Control Three Point
Accommodates a variety of implement needs



Electric Engaged Independent PTO
Readily available to the operator to control PTO implements



Power Shuttle Transmission
Enables fast and efficient directional changes (CPS) model only)



540/750/1000 PTO
Provides compatibility to a large number of implementst



Hand Clutch
The hand clutch button added to the gear control lever enables you to change gears easily



Premium Seat
The air suspension seat with 10 degree swivel for added comfort



Right-Side Door and Steps
Provides access to both sides of the cab

RECOMMENDED IMPLEMENTS / ATTACHMENTS



LOADER
High capacity with an abundance of standard features



LAND GRADER
Heavy steel construction, high strength designed for use in demanding applications



ROTARY CUTTER
Durable heavy steel design providing quality and strength



BOX BLADE
Features a heavy welded steel design for use in demanding applications

MT573C / MT573CPS SPECIFICATIONS

CATEGORY		
ENGINE	MT573C	MT573CPS
Type	Vertical Water-cooled 4 Cylinder Diesel Engine	Vertical Water-cooled 4 Cylinder Diesel Engine
Model	L4C25-T	L4C25-T
Emission	EPA Tier 4F	EPA Tier 4F
Engine HP (kW)	73 (54.4)	73 (54.4)
PTO (HP)	62	62
Rated Speed (rpm)	2,500	2,500
Displacement (in ³ .)	152.9	152.9
Fuel Tank Capacity (gal.)	26.4	26.4
DRIVE TRAIN		
Transmission Type (Option)	Synchro Shuttle	Synchro Shuttle
No. Of Speed	F20 x R20	F20 x R20
Forward Speed (mph)	0.11 - 19.4	0.11 - 19.4
PTO		
Type	Independent	Independent
Rear (rpm)	540 / 750 / 1,000	540 / 750 / 1,000
HYDRAULIC SYSTEM		
Control System	Position / Draft	Position / Draft
Implement Pump (gpm)	13.2	13.2
Steering Pump (gpm)	6.6	6.6
Total Flow (gpm)	19.8	19.8
Category (3pt Hitch)	CAT II	CAT II
Hitch Lift Capacity (lbs.) (Hitch End)	6,614	6,614
Remote Ports	3 Pairs (Front), 3 Pairs (Rear)	3 Pairs (Front), 3 Pairs (Rear)
DIMENSION		
Overall Length (Frame To Link in.)	150	150
Overall Width With Tires (in.)	77.5	77.5
Wheelbase (in.)	84.6	84.6
Height To Top (in.)	104.4	104.4
Total Weight w/o Ballast (lbs.)	6,620	6,620
TIRE SIZE		
Front / Rear R14	W320/85R24 122D	W460/85R30 145D
Front / Rear Ag	11.2 – 24	16.9 – 30

*All specs and features are subject to change, and pictures could include optional equipment etc.

FRONT END LOADER	LL6100
TRACTOR APPLICATION	MT5 SERIES
Bucket Size (in.)	78
Maximum Lift Height (in.)	126.5
Clearance With Attachment Dump (in.)	95.3
Reach At Maximum Height (in.)	5.7
Maximum Dump Angle (deg.)	64
Maximum Rollback Angle (deg.)	38
Digging Depth (in.)	7.0
Overall Height In Carry Position (in.)	64.2
Lift Capacity (At Pivot Pin) (lbs.)	3,626
Breakout Force (At Pivot Pin) (lbs.)	6,644
Approx. Weight (Loader w/o Bucket) (lbs.)	1,232

- Additional Equipment Available
- Power & Tilt Steering
 - Switch Operated Independent PTO
 - Front Loader Valve And 3rd Function Joystick
 - Swivel Air Suspension Adjustable Seat (Cab Model)
 - Deluxe Stereo System
 - 7 Pin Electrical Connector
 - Hydraulic Draft & Position Control With Auto Lift
 - High Beam Operation / Warning Lights

