

UTILITY TRACTORS | 73.7 HP – 100.6 HP

MT7 SERIES

START BLUE. STAY BLUE.

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

LS Tractor

5-year limited warranty.
See dealer for details.



LS Tractor
Start Blue. Stay Blue.

MT7 SERIES

HIGHER STANDARDS. LOWER ISSUES.

Maintaining your land to your standards takes a tractor and attachments made to ours. And with a five-year limited powertrain warranty on the MT7, you'll be well taken care of as well.



HIGH CAPACITY LOADER
Increased lift capacity for heavy duty jobs.



GOODYEAR LSW TIRES
Help equipment operators unlock greater productivity while taking on some of the toughest jobs.



SPACIOUS PANORAMIC CAB
Help equipment operators unlock greater productivity while taking on some of the toughest jobs.



GRILL GUARD
Standard with optional Loader to protect your equipment from debris.




HIGH LIFT CAPACITY 3-POINT HITCH
Powerful 3-point lift capacity to unleash your implements potential.



POWER SHUTTLE TRANSMISSION
With electronic lever providing smooth and easy shifting.



AGRESSIVE STYLING
Upgraded, modern look where form meets function.



STANDARD REAR WORK LIGHTS
Four work lights provide excellent illumination.



LED HEADLIGHTS
For high visibility in low light conditions.

RECOMMENDED IMPLEMENTS / ATTACHMENTS



LOADER
High capacity with an abundance of standard features



LAND GRADER
Heavy steel construction, high strength designed for use in demanding applications



ROTARY CUTTER
Durable heavy steel design providing quality and strength



BOX BLADE
Features a heavy welded steel design for use in demanding applications

MT7 SERIES SPECIFICATIONS

	MT774CPS	MT7101CPS
Type	Cabin	Cabin
ENGINE		
Type	4 Cylinder, CRDI, Water-cooled	4 Cylinder, CRDI, Water-cooled
Model	F34-55kW	F5G-75kW
Engine HP (kW)	73.7 (55)	100.6 (75)
PTO HP	65.6	85.5
Rated Speed, rpm	2,200	2,200
Displacement (in³)	206.7	206.7
Fuel Tank Capacity (gal.)	30.4	30.4
DRIVE TRAIN		
Transmission	Power Shuttle	Power Shuttle
No. Of Speed	24 X 24	24 X 24
Brakes	Wet, Multi - disc	Wet, Multi - disc
Forward Speed (mph)	0.9 - 20.8	1 - 23.1
PTO		
Type	Independent	Independent
Rear (rpm)	540 / 750 / 1,000	540 / 750 / 1,000
HYDRAULIC SYSTEM		
Control System	Position / Draft	Position / Draft
Implement Pump (gpm)	15.7	15.7
Steering Pump (gpm)	6.5	6.5
Total Flow (gpm)	22.2	22.2
Category (3pt Hitch)	CAT II	CAT II
Hitch Lift Capacity (lb.)	7,275	8,378
Remote Valves	3 Pairs (Front) 2 Pairs (Rear)	3 Pairs (Front) 2 Pairs (Rear)
DIMENSION		
Overall Length, Frame To Link (in.)	152.2	152.2
Overall Width, Tires (in.)	78.7	78.7
Wheelbase (in.)	90	90
Height To Top (in.)	105	107
Total Weight W/O Ballast (lbs.)	7,827	7,985
TIRE SIZE		
Front / Rear R14	FW: 320/85R24, RR: 460/85R30	FW: 340/70R28, RR: 460/75R38
Front / Rear Ag	F: 11.2 – 24, R: 16.9 – 30	F: 13.6-24, R: 18.4-34

FRONT END LOADER	LL8100
TRACTOR APPLICATION	MT7 SERIES
Bucket Size (in.)	83
Maximum Lift Height (in.)	139.9
Clearance With Attachment Dump (in.)	103.3
Reach At Maximum Height (in.)	23.4
Maximum Dump Angle (deg.)	57
Maximum Rollback Angle (deg.)	46
Digging Depth (in.)	4.6
Overall Height In Carry Position (in.)	68.8
Lift Capacity (At Pivot Pin) (lbs.)	5,139
Breakout Force (At Pivot Pin) (lbs.)	5,313
Approx. Weight (Loader W/O Bucket) (lbs.)	1,660

