

COMPACT TRACTORS | 25 HP - 42 HP

MT2E | MT2 SERIES



LS Tractor
Start Blue. Stay Blue.

MT2E | MT2 SERIES

HIGHER STANDARDS. LOWER ISSUES.

Maintaining your land to your standards takes a tractor and attachments made to ours. And with a six-year limited powertrain warranty on most models, you'll be well taken care of as well.



NEW LS FAMILY LOOK

Upgraded, modern look also provides better functionality



LED LIGHTS

Increased visibility while increasing efficiency



LARGER TIRE SIZE AND OPTIONS

Enhanced traction and stability with more options



BETTER VISIBILITY

Cab redesign allows for better operator visibility



LOADER LIFT CAPACITY INCREASE

Do more work easily



TF-LCD PANEL

Shows regen time, oil change intervals and more



IMPROVED SEAT COMFORT

So you can stay more comfortable for longer



UPGRADED ERGONOMIC CONTROLS

Refined controls make for easier operation



NEW DEEP SKY BLUE PAINT

Elevated look with silver rims

RECOMMENDED IMPLEMENTS / ATTACHMENTS



LOADER

High capacity with an abundance of standard features



BACKHOE

Excellent capacity, smooth and consistent operation for added control



ROTARY CUTTER

Durable heavy steel design providing quality and strength



BOX BLADE

Features a heavy welded steel design for use in demanding applications

MT2E / MT2 SPECIFICATIONS

MODEL	MT226ED	MT226E	MT226HE	MT232E	MT232HE	MT242E	MT242HE	MT226HEC	MT232HEC	MT242HEC	MT232H	MT242H	MT232HC	MT242HC
Type	ROPS Type	ROPS Type	ROPS Type	ROPS Type	ROPS Type	ROPS Type	ROPS Type	Cabin Type	Cabin Type	Cabin Type	ROPS Type	ROPS Type	Cabin Type	Cabin Type
ENGINE														
Type (Liquid-cooled Diesel)	3 Cylinder, NA, IDI	3 Cylinder, NA, IDI	3 Cylinder, NA, IDI	3 Cylinder, NA, CRDI	3 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI	3 Cylinder, NA, CRDI	3 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI	3 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI	3 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI
Model (Tier 4)	MHI S3L2-W463G-TAC	MHI S3L2-W463G-TAC	MHI S3L2-W463G-TAC	YANMAR 3TN-V88C-MLST	YANMAR 3TN-V88C-MLST	YANMAR 4TN-V88C-MLST	YANMAR 4TN-V88C-MLST	YANMAR 3TNV88F-EPLST	YANMAR 3TNV88C-MLST	YANMAR 4TNV88C-MLST	YANMAR 3TNV88C-MLST	YANMAR 4TNV88C-MLST	YANMAR 3TNV88C-MLST	YANMAR 4TNV88C-MLST
Engine HP (gross)	24.6	24.6	24.6	31.7	31.7	42.5	42.5	24.4	31.7	42.5	31.7	42.5	31.7	42.5
PTO (HP)	19.2	19.2	17.1	28.5	26.2	35.4	34.8	19	26.2	34.8	26.2	34.8	26.2	34.8
Rated Speed (rpm)	2,500	2,500	2,500	2,600	2,600	2,600	2,600	2,400	2,600	2,600	2,600	2,600	2,600	2,600
Displacement (in.3.)	80.4	80.4	80.4	100.2	100.2	133.6	133.6	100.2	100.2	133.6	100.2	133.6	100.2	133.6
Fuel Tank Capacity (gal.)	10.6	10.6	10.6	10.6	10.6	10.6	10.6	11.4	11.4	11.4	10.6	10.6	11.4	11.4
Alternator V-A	12V - 50 Amps	12V - 50 Amps	12V - 50 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps
DRIVE TRAIN														
Transmission	Synchro Shuttle	Synchro Shuttle	HST	Synchro Shuttle	HST	Synchro Shuttle	HST	HST	HST	HST	HST	HST	HST	HST
No. Of Speed	F12 X R12	F12 X R12	3 Ranges	F12 X R12	3 Ranges	F12 X R12	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges
Brakes	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc
Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
PTO														
Type	TM Driven	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent
Rear (rpm)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)
HYDRAULIC SYSTEM														
Control System	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position
Implement Pump (gpm)	79	79	71	74	6.7	74	6.7	6.1	6.7	6.7	6.7	6.7	6.7	6.7
Steering Pump (gpm)	4.6	4.6	4.6	5	5	5	5	4.6	5	5	5	5	5	5
Total Flow (gpm)	12.5	12.5	11.7	12.4	11.7	12.4	11.7	10.7	11.7	11.7	11.7	11.7	11.7	11.7
Category (3pt Hitch)	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I
Hitch Lift Capacity Hitch End (lbs.)	1,433	1,433	1,433	1,433	1,433	1,433	1,433	1,433	1,433	1,433	1,433	1,433	1,433	1,433
Remote Valves	Option	Option	Option	Option	Option	Option	Option	1pair	1pair	1pair	1pair	1pair	1pair	1pair
DIMENSION														
Overall Length (Frame To Link, in.)	119	119	119	125	125	125	125	125	125	125	125	125	125	125
Overall Width With Tires (in.)	66	66	66	66	66	66	66	66	66	66	66	66	66	66
Wheelbase (in.)	66	66	66	69	69	74	74	69	69	74	69	74	69	74
Height To Top ROPS (in.)	95	95	95	95	95	95	95	90	90	90	95	95	90	90
TIRE SIZE														
Front / Rear Ag	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24
Front / Rear Industrial	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20
Front / Rear VT	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20
Front / Rear Turf	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20
WEIGHT														
Total Weight w/o Ballast (lbs.)	2963	2985	3007	3166	3210	3250	3294	3609	3677	3761	3254	3338	3721	3805

FRONT END LOADER	LL3001, LL3002	LL3003
MATCHING TRACTOR	MT226E (ROPS, CAB)	MT232E, MT242E, MT232, MT242
Bucket Size (in.)	66	66
Maximum Lift Height (in.)	94.3	94.3
Clearance With Attachment Dump (in.)	67	67
Reach At Maximum Height (in.)	14.4	14.4
Maximum Dump Angle (deg.)	48	48
Maximum Rollback Angle (deg.)	42.5	42.5
Digging Depth (in.)	4.8	4.8
Overall Height In Carry Position (in.)	51.2	51.2
Lift Capacity (At Pivot Pin, 1.5m) (lbs.)	1,965	2,506
Breakout Force (At Pivot Pin) (lbs.)	2,962	3,723
Approx. Weight (Loader w/o Bucket) (lbs.)	741	741

BACKHOE	LB3001, LB3002
TRACTOR APPLICATION	MT226E (ROPS), MT226E (CAB), MT232E, MT242E, MT232, MT242
Digging Depth (in.)	97.2
Reach From Centerline Of Swing Pivot (in.)	127.2
Loading Height (in.)	76.2
Swing Arc (deg.)	160
Transport Height (in.)	81.8
Bucket Rotating (deg.)	180
Stabilizer Spread (Down Position) (in.)	67.5
Stabilizer Spread (Up Position) (in.)	50
Bucket Digging Force (lbs.)	3,663

**All specs and features are subject to change, and pictures could include optional equipment etc.*

Additional Equipment
• Standard Rear Work-light, ROPS and Cab
• Standard Drawbar

START BLUE. STAY BLUE.

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

LS Tractor

6-year limited warranty.
See dealer for details.


