

SMALL COMPACT TRACTOR | 24.7 HP

# XJ SERIES



**LS** Tractor  
Start Blue. Stay Blue.



**XJ SERIES**

# HIGHER STANDARDS. LOWER ISSUES.

Maintaining your land to your standards takes a tractor and attachments made to ours. And with a six-year limited powertrain warranty on most models, you'll be well taken care of as well.



#### **Electric PTO Engagement**

Provides added comfort



#### **Illuminated Dash with Digital RPM**

Provides excellent operator visibility



#### **Engine Compartment Access**

Excellent access for preventative maintenance



#### **Foldable ROPS**

Provides versatility



#### **Standard Toolbox**

Providing storage




#### **Durable Front Loader and Bucket**

High-quality and durable front bucket



#### **Durable and Adjustable Three Point**

Provides 1,433 lbs. of lift capacity



#### **High Capacity Front Loader**

Features 1,276 lbs. of lift capacity at pivot pins



#### **Multiple Tire Options Available**


Provides tires for nearly all applications

## RECOMMENDED IMPLEMENTS / ATTACHMENTS



#### **LOADER**

High capacity with an abundance of standard features



#### **BACKHOE**

Excellent capacity, smooth and consistent operation for added control



#### **ROTARY CUTTER**

Durable heavy steel design providing quality and strength



#### **BOX BLADE**

Features a heavy welded steel design for use in demanding applications

# XJ2025H

# SPECIFICATIONS

CATEGORY	
ENGINE	XJ2025H
<b>Type</b>	3 Cylinder-Indirect - injection, Water-cooled
<b>Model (Tier 4)</b>	Mitsubishi S3L2
<b>Engine HP (gross)</b>	24.7
<b>PTO (HP)</b>	18.5
<b>Rated Speed (rpm)</b>	2,500
<b>Displacement-cu (in<sup>3</sup>.)</b>	80.4
<b>Fuel Tank Capacity (gal.)</b>	6.6
<b>Alternator (V-A)</b>	12 - 50
DRIVE TRAIN	
<b>Transmission</b>	Hydrostatic Drive
<b>No. Of Speed</b>	2 Ranges
<b>Brakes</b>	Wet, Multi-disc
PTO	
<b>Type</b>	Independent
<b>Rear (rpm)</b>	Standard (540 rpm)
<b>Mid (rpm)</b>	Standard (2,000 rpm)
HYDRAULIC SYSTEM	
<b>Lift Control System</b>	Position
<b>Implement Pump (gpm)</b>	5.9
<b>Steering Pump (gpm)</b>	2.6
<b>Steering</b>	Hydrostatic Power Steering
<b>Total Flow (gpm)</b>	8.5
<b>Category (3pt Hitch)</b>	CAT I
<b>Hitch Lift Capacity (lbs.) (Hitch End)</b>	1,433
DIMENSION	
<b>Overall Length (Bumper To Link in.)</b>	103
<b>Overall Width With Tires (in.)</b>	44.9
<b>Wheelbase (in.)</b>	59
<b>Height To Top Of ROPS (in.)</b>	84.5
TIRE SIZE	
<b>Front / Rear Industrial</b>	23 x 8.5 - 12 / 33 x 12 - 16.5
<b>Front / Rear Turf</b>	23 x 8.5 - 12 / 33 x 12 - 16.5
WEIGHT	
<b>Total Weight w/o Ballast (lbs.)</b>	1,689

SNOW BLOWER	
LS3150	
TRACTOR APPLICATION	XJ SERIES
<b>Overall Width (in.)</b>	50
<b>Cutting Width (in.)</b>	49 3/4
<b>Cutting Height (in.)</b>	20
<b>Impeller Drive</b>	Chain #40
<b>Auger Drive</b>	Worm Gear
<b>Auger Diameter (in.)</b>	12 3/4
<b>Impeller Diameter (in.)</b>	15 3/4
<b>Number Of Blades On Impeller</b>	3
<b>Chute Rotation (deg.)</b>	Manual
<b>Adjustable Heavy Skid Shoes</b>	Yes

FRONT END LOADER	
LL2102	
TRACTOR APPLICATION	XJ SERIES
<b>Bucket Size (in.)</b>	50
<b>Maximum Lift Height (in.)</b>	85.7
<b>Clearance With Attachment Dump (in.)</b>	63.3
<b>Reach At Maximum Height (in.)</b>	25.1
<b>Maximum Dump Angle (deg.)</b>	50
<b>Maximum Rollback Angle (deg.)</b>	38
<b>Digging Depth (in.)</b>	3.7
<b>Overall Heights In Carry Position (in.)</b>	43.2
<b>Lift Capacity (@ Pivot Pin, 1.5m height) (lbf)</b>	1,111
<b>Lift Capacity (@ Pivot Pin, Max height) (lbf)</b>	1,091
<b>Breakout Force (At Pivot Pin) (lbs.)</b>	1,426
<b>Approx. Weight (Loader w/o Bucket) (lbs.)</b>	580

BACKHOE	
LB1104	
TRACTOR APPLICATION	XJ SERIES
<b>Digging Depth (in.)</b>	79.3
<b>Reach From Centerline Of Swing Pivot (in.)</b>	113.3
<b>Loading Height (in.)</b>	56.9
<b>Swing Arc (deg.)</b>	150
<b>Transport Height (in.)</b>	75.3
<b>Bucket Rotating (deg.)</b>	163
<b>Stabilizer Spread (Down Position) (in.)</b>	87.8
<b>Stabilizer Spread (Up Position) (in.)</b>	55.7
<b>Bucket Digging Force (lbs.)</b>	2,097

MID-MOUNT MOWER	
LM3560	
TRACTOR APPLICATION	XJ SERIES
<b>Cutting Width (in.)</b>	60
<b>Overall Width (in.)</b>	74
<b>Cutting Height Range (in.)</b>	1 to 4-1/8
<b>Deck Shell Thickness</b>	10-Gauge (0.1345 in.) Grade 50 Sheet
<b>Spindle Speed At Rated Engine(rpm)</b>	2,842
<b>Blade Tip Speed (ft./min)</b>	18,000
<b>Number Of Blades</b>	3
<b>Blade Length (in.)</b>	21
<b>Blade Width (in.)</b>	2- 1/2
<b>Blade Thickness (in.)</b>	1/4
<b>Shipping Weight Of Base 60" Deck (lbs.)</b>	450

## Additional Equipment

- Power Steering
- Switch Operated Independent PTO, Rear & Mid (XJ2025)
- Foldable ROPS
- Rear Work light
- Hydraulic Position Control
- Differential Lock
- Draw bar
- Pre-Heat Starting Aid
- Safety Flashers & Turn Signals
- Fuel, Coolant Temperature, Tachometer & Hour Meter Gauges
- Pre-Heating, Parking Brake, Battery Charging, Engine Oil Pressure, PTO Operation And High Beam Operation And Warning Lights

*\*All specs and features are subject to change, and pictures could include optional equipment etc.*

# START BLUE. STAY BLUE.

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | [LSTractorUSA.com](http://LSTractorUSA.com)  
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

## LS Tractor

6-year limited warranty.  
See dealer for details.



---

---

---

---